








Rotating Eyebolts and weld-on points









	C800	C800X	C811X H.T.	C813X	C806X H.T.	C807X H.T.	C6X807 H.T.
Made in Italy							
Swivel under load	✓	✓					
360° rotation before applying a load	✓	✓	✓	✓	✓	✓	✓
Self-aligning pivoting bail at 180°	✓	✓	✓	✓			
Pull at 90° with minimum dimensions (for confined spaces)	✓	✓			✓	✓	✓
Design factor 4:1	✓	✓		✓	✓	✓	✓
Design factor 5:1			✓				
DGUV Type-approval*	✓	✓				✓	
14462 Duplex Stainless steel**							✓
Long bolt on demand	✓	✓	✓	✓	✓		
Grade	80	100	100	100	100	100	60

*The German DGUV Institute certifies these items are produced according to GS-HM 36:2021 (former GS-OA 15-04:2020) standard.



**14462 duplex is superior to 316L and 316Ti in corrosion resistance

Rotating Eyebolts and weld-on points

	C815X	C816X	C832X	C820X	C830X	C810X	C810FX	C817X
Made in Italy								
Swivel under load	✓	✓						✓
360° rotation before applying a load	✓	✓				✓	✓	✓
Self-aligning pivoting bail at 180°	✓	✓		✓	✓			
Pull at 90° with minimum dimensions (for confined spaces)	✓							
Design factor 4:1	✓	✓	✓	✓	✓	✓	✓	✓
Weld-on	✓		✓	✓	✓			
DGVU Type-approval*	✓	✓	✓	✓	✓	✓	✓	✓
Long bolt on demand						✓		
Grade	100	100	100	100	100	100	100	100

*The German DGVU Institute certifies these items are produced according to GS-HM 36:2021 (former GS-OA 15-04:2020) standard.



**14462 duplex is superior to 316L and 316Ti in corrosion resistance