



MA Series Hoist

Hand Chain Hoist

1/2 to 30 Metric ton Capacity

FEATURES

- ▶ Increased efficiency by additional pinion shaft bearing and close tolerances.
- ▶ Hook blocks are bolted, allowing complete hook inspection.
- ▶ Lightweight and durable all steel construction with powder coated finish and plated frame components to resist corrosion.
- ▶ Premium USA Made Grade 80 Zinc plated alloy load chain.
- ▶ Hand chain opening is formed with a radius for smooth operation.
- ▶ Sealed ball bearings on the chain wheel maximize efficiency and serviceability.
- ▶ Self-adjusting double pawl disc type mechanical load brake ensures positive load control.
- ▶ Double roller guide ensures load chain tracking.
- ▶ Optional Overload Protection is a one directional clutch that will only slip in the lift direction.
- ▶ Meets: ASME/ANSI B30.16, OSHA, NASA-STD-8719.9
- ▶ ATEX rated II 3 GD c IIB 54° C X for limited use in hazardous environments.



Final assembly and re-testing in the USA



Plated Frame and Guide Components with Rounded Hand Chain Entrance

Zinc Plated Chains



Before using these products; read and follow instructions in the operator's manual. Never exceed capacity. Do not use for lifting people or loads over people.

